

# Material Safety Data Sheet (91/155/EWG)

page 1/4  
Date of issue: January 18, 2002

---

Trade Name: LUKAS shellac in alkohol, article no. 2364, 2365, 2366

---

## 1. Identification of the substance, preparation and the company:

Trade Name: LUKAS shellac in alkohol, article no. 2364, 2365, 2366

Manufacturers Name: LUKAS Künstlerfarben & Maltuchfabrik,  
Dr. Fr. Schoenfeld GmbH & Co.

Manufacturers Address: Harffstr. 40  
40591 Düsseldorf - Germany

phone: ++49-211-78130

fax: ++49-211-781329

emergency Phone: ++49-211-781340 (LUKAS laboratory)

---

## 2. Composition / Information on Ingredient:

Content (%)	CAS-No.	Symbol	Risk-phrases	Substance
(1) 66	64-17-5	F	11	ethanol

additional information regarding the chemical characterization: solution of leaf shellac in ethanol.

---

## 3. Health Hazard Data:

F Highly flammable  
R 11: Highly flammable.

---

## 4. First Aid Measures:

*In general:* Remove all contaminated clothing immediately.

*Inhalation:* Move to a well ventilated area. If unconscious, seek medical attention.

*Skin Contact:* Wash skin with soap and water for 5 minutes. Seek medical attention if skin-irritation persists.

*Eye Contact:* Remove all eyewear. Rinse eyes thoroughly (5 – 10 minutes) with water. Seek medical attention if irritation develops.

*Ingestion:* If swallowed, do not induce vomiting. Call a physician or poison control center immediately. Get prompt medical attention. If symptoms occur, move to fresh air. If symptoms persist, see a physician.

---

## 5. Fire Fighting Measures:

*Extinguishing Media:* water fog, water mist.

*Not recommended for security reasons:* full power water jet, CO2.

*Particular danger caused by material, its combustion products or gases:* may form explosive gas air mixture.

*Proper Protective Equipment:* protective clothing and a self-contained breathing apparatus.

---

# Material Safety Data Sheet (91/155/EWG)

page 2/4  
Date of issue: January 18, 2002

---

Trade Name: LUKAS shellac in alkohol, article no. 2364, 2365, 2366

---

## 6. Accidental Release Measures

*Air:* not applicable  
*Water:* Avoid entry into water and sewage systems. Pay attention to local official rules.  
Contain contaminated extinguished water.  
*Ground:* Pick up product with liquid-binding material (sand, acid-binder, universal-binder, sawdust)

Contaminated material should be disposed as mentioned under point 13. Ensure good ventilation.

---

## 7. Handling and Storage

*7.1 Handling:* Handling as usual for working with chemicals:  
Keep away from food and drinks.  
Avoid open fire as product is flammable.  
Do not store or use near heat or flame.  
Use exhaust fan to admire adequate cross ventilation.

*7.2 Storage:* Store in a cool area and avoid direct sunlight.  
Avoid release to the environment.  
Keep out of reach of children.  
Storage class: VbF: BI

---

## 8. Exposure Controls / Personal Protection

*8.1 Additional hints to the formation of technical installations:* Use only in well ventilated areas.

*8.2 Components with work-place related limits to be monitored:*  
See name and CAS no. under point 2.

No.	Type	Value	Unit
(1)	MAK	1000	ml/m <sup>3</sup> (ppm)

---

## 9. Physical and Chemical Properties

Form: liquid  
Colour: yellowish - redish  
Odour: characteristic  
pH value: not applicable  
Melting Point: not applicable  
Boiling Point: 78 °C (solvent)  
Flash Point: approx. 14,5°C  
Ignition Temperature: 425 °C (solvent)  
Explosion Limits: lower explosion limit (%): 3,5 % (solvent)  
upper explosion limit (%): 15,0 % (solvent)  
Density: 0,91 g/ml (20 °C)  
Solubility in Water: mixable

# Material Safety Data Sheet (91/155/EWG)

page 3/4  
Date of issue: January 18, 2002

---

Trade Name: LUKAS shellac in alkohol, article no. 2364, 2365, 2366

---

## 10. Stability and Reactivity

*Conditions to avoid:* No decomposition when stored and handled correctly.  
*Dangerous reactions:* May cause with air an explosive steam-air-mixture.

---

## 11. Toxicological Information

There are no data available on the preparation itself.

LD (oral, human): 6000 mg/kg; LD.50 (oral, ratt): 7060 mg/kg (ethanol)  
*Skin effects:* irritating; can cause dry skin.  
*Eye Effects:* irritation to eyes possible.

---

## 12. Ecological Information

There are no data available on the preparation itself.

*General hint:* The product should not be allowed to enter drains or water courses.  
Water hazard classs (German regulation) 1 (self-assessment): slightly hazardous for water.  
Avoid entry into water, ground and sewage systems.

---

## 13. Disposal Considerations

Pick up spilled quantities with universal-binder (kieselguhr) or sand. Dispose of this material and its container at hazardous or special waste collection points. Do not dispose with household waste. Avoid entry into sewage system.

---

## 14. Transport Information:

### 14.1 Road Transportation:

*Class/Cipher/Letter:* class 3, cipher 3 b  
*IMDG:* UN number: 1170  
*Danger Activator:* alcohol

### 14.2 Inland Navigation Transportation:

*Class/Cipher/Letter:*

### 14.3 Ocean Navigation Transportation:

*Class:* class 3.2, page 3219  
*IMDG:* packing group: II

*EMS-number:* 3-06  
*MFAG:* 305

### 14.4 Air Transportation:

*Class:* class 3

### 14.5 Additional Comments:

*Correct technical name:* alcohol solution

# Material Safety Data Sheet (91/155/EWG)

page 4/4  
Date of issue: January 18, 2002

---

Trade Name: LUKAS shellac in alcohol, article no. 2364, 2365, 2366

---

## 15. Regulatory Information:

Labelling after EC regulations:

*Danger Description:* F Highly flammable

*Product includes:* alcohol

Risk-Phrases:

R 11: highly flammable

*Additional details:* packing with child-safety-stopper

---

## 16. Other Information

The purpose of this Safety Data Sheet is to describe our product with respect to possible safety issues and requirements. All data presented has been prepared using our most recent knowledge and experience, and is not meant to be a guarantee of the products' properties.